

Barb-Sert Standard Sizes

Inch Sizes		Metric Sizes		D Diameter	L Length		H Recommended Hole Diameter	W Recommended Minimum Wall Thickness	Barb-Sert Part Number English (IBSE)
Internal Thread Size	Basic Part Number	Internal Thread Size	Part Number		Regular	Short			Barb-Sert Part Number Metric (IBSM)
2-56	B08656-30	M2 x 0.4	B02545-30	.173	.205		.159	.067	IBSE-086-056-1-301-00-00
2-56	BS08656-30	M2 x 0.4	BS02545-30	.173		.160	.159	.067	IBSE-086-056-3-301-00-00
4-40	B11240-30	M3 x 0.5	B03050-30	.173	.205		.159	.067	IBSE-112-040-1-301-00-00 IBSM-030-050-1-301-00-00
4-40	BS11240-30	M3 x 0.5	BS03050-30	.173		.160	.159	.067	IBSE-112-040-3-301-00-00 IBSM-030-050-3-301-00-00
6-32	B13832-30	M3.5 x 0.6	B03560-30	.217	.276		.196	.089	IBSE-138-032-1-301-00-00 IBSM-035-060-1-301-00-00
6-32	BS13832-30	M3.5 x 0.6	BS03560-30	.217		.160	.196	.089	IBSE-138-032-3-301-00-00 IBSM-035-060-3-301-00-00
8-32	B16432-30	M4 x 0.7	B04070-30	.250	.335		.229	.098	IBSE-164-032-1-301-00-00 IBSM-040-070-1-301-00-00
8-32	BS16432-30	M4 x 0.7	BS04070-30	.250		.217	.229	.098	IBSE-164-032-3-301-00-00 IBSM-040-070-3-301-00-00
10-24	B19024-30	M5 x 0.8	B05080-30	.280	.395		.255	.114	IBSE-194-024-1-301-00-00 IBSM-050-080-1-301-00-00
10-24	BS19024-30	M5 x 0.8	BS05080-30	.280		.257	.255	.114	IBSE-194-024-3-301-00-00 IBSM-050-080-3-301-00-00
10-32	B19032-30			.280	.395		.255	.114	IBSE-190-032-1-301-00-00
10-32	BS19032-30			.280		.257	.255	.114	IBSE-190-032-3-301-00-00
1/4-20	B25020-30	M6 x 1.0	B06010-30	.335	.500		.320	.130	IBSE-250-020-1-301-00-00 IBSM-060-010-1-301-00-00
1/4-20	BS25020-30	M6 x 1.0	BS06010-30	.335		.296	.320	.130	IBSE-250-020-3-301-00-00 IBSM-060-010-3-301-00-00